

MED0374GD | Bromic MediFridge™ Display Chiller 374L

Audible Alarm sounds if the temperature of the unit falls or rises outside the set Min/Max recording

Integrated lock keeps medicines Fan forced to keep even temperature cooling throughout the unit



Door open alarm

Fan and evaporator protection cover prevents product from being damaged LED Light maximises product


visibility


Double glazed safety glass increases energy efficiency


PVC coated elevated bottom shelf for consistent temperature airflow

Rollers for easy placement

Adjustable legs for levelling







Integrated temperature Alarm System ensures sensitive stock is maintained and managed according to requirements

Fan Forced air circulation ensures even temperature throughout the unit

Increased air circulation around the unit thanks to unique custom wire 'open rung' shelves at the top and bottom to prevent overstocking

Consistent air circulation throughout the unit ensures mandated temperatures of 2°C to 8°C

Backed by Bromic national services & warranty

2
0
<u>S</u>
Ē
$\stackrel{>}{=}$
ш

	External (mm)	Internal (mm)
Height	1840	1555
Width	595	505
Depth	598	462



MED0374GD | Bromic MediFridge™ Display Chiller 374L

SPECIFICATIONS

Part Number	3736218	E	xternal (mm)	Internal (mm)		
Capacity	372L	Height	1840	1555		
Weight	81kg	Width	595	505		
Air Circulation	Fan-Forced	Depth	598	462		
Climate Class	4					
	Range	+2°C to 8°C	+2°C to 8°C			
Temperature	Min/Max Temp Recorder	Yes	Yes			
	Display	Digital	Digital			
Exterior	Material	Powder Coa	Powder Coated Sheet Metal			
	Solid or Glass	Low-E Glass	Low-E Glass + Argon Gas			
	Shape	Flat	Flat			
	Self-Closing	Yes	Yes			
Door	Door Lock	Yes	Yes			
	Door Switch	Yes	Yes			
	Door Swing Dimension	595mm	595mm			
	Total Depth of Door Open	1193mm	1193mm			
	No. of Shelves	6 (5 full size	6 (5 full size, 1 floor shelf)			
	Style of Shelves	Open rung s	Open rung shelf			
Shelves	Shelves Dimensions	500 x 400m	500 x 400mm			
	Adjustable	Yes	Yes			
	Capacity	20kg	20kg			
Electrical	Voltage	240V	240V			
	Frequency	50Hz	50Hz			
	Input Power	350W	350W			
	Current	2.7A	2.7A			
	Power Consumption	2.37kWh/24	2.37kWh/24hr			
Compressor	Refrigerant	R134a	R134a			
	Charge	200g	200g			
Alarms	Temperature	Yes	Yes			
	Audible	Yes	Yes			
Internal Lighting	LED Internal Light	Yes	Yes			
Defrost	Manual/Automatic	Automatic	Automatic			
	Type of Defrost System	OFF Cycle	OFF Cycle			
Plug	Туре	3-pin AU plu	3-pin AU plug			
	Rated Current	10A	10A			
	Plug Location	Rear, botton	Rear, bottom left			
Insulation Type	Cyclopentane					
Feet/Wheels	2 rollers at rear, 2 feet at front	2 rollers at rear, 2 feet at front				
Approvals	Quality Care Pharmacy Program Compliance - Cold Chain Testing (QCPP), MEPS, The Pharmacy Guild of Australia					
Warranty	5 year warranty					
Data Logger	Available, part #350700050					